



### **Bubler 25**

Designed for water purification of bulk water storage tanks up to 1000 gallons. The Bubler 25 is supplied in a plastic splash-proof enclosure that can be wall mounted outdoors. The Bubler 25 has its own air compressor capable of 2.5 liters per minute that can pump ozone into a tank, tub, or pond up to 24 hours a day independent of water circulation pumps. The Bubler 25 is typically installed with the included weighted airstone kit, or optional ozone injection manifold for larger tanks or ponds.

Ozone does not change the PH of the water. Ozone dissolved in water will not irritate skin, nose or ears nor does it leave any chemical residue.

### **Specifications:**

- \* Dimensions: 9 1/2" x 8 1/2" x 4 1/2"
- \* Input Voltage: 120 VAC, 60 Hz
- \* Operating Current: .67 Amperes
- \* Ozone Generation: Corona Discharge
- \* Ozone Output: 0.25 Grams per Hour
- \* Power Consumption: 80 Watts
- \* Air Compressor: 2.5 LPM
- \* Shipping Weight: 6 pound

### **Operation:**

- " Insert Blue Polyurethane tube into ozone outlet at black Kynar check valve
- \* Attach weighted airstone to other end of Blue Poly tube.
- \* Insert airstone into water tank 2/3<sup>rd</sup> of level.
- \* Plug into 110vac GFI circuit
- \* For tanks a timer may be used to control dosage.  
For example a smaller tank could run (on 30 minutes off 3 hours ...) to destroy bacteria and other biologicals in water.

Options: Ozone Injection Manifold