



New Source Membrane Filter

Self-Contained unit with stainless steel frame, pump and motor with inlet strainer, controls, gauges, and membrane filter tubes. Provides good, clear pre-rinse or clean high quality wash water. Simple reliable and requires virtually very little maintenance.

*Frame is 304 stainless steel
Filter Elements are UF membranes that remove particulate larger than .02 microns from dirty sump water.*

Specifications:

Filtration system

- * H: 102" W: 44" D: 34"
- * weight 575 lb (shipping weight 625 lb)
- * pump hp: 3
- * voltage 208/230/480 volt, 3 phase @ 9 / 8 / 4.7 amp
- * Control Power: 115 vac, 5 amp max
- * On/Off Control: Switch selectable Off/On or remote
- * 12 membrane system 1500 GPD (gallons per day)
- * 18 membrane system 2200 GPD
- * 24 membrane system 3600 GPD
- * Inlet filtration: Cleanable Basket Strainer
- * Filtration: .02 micron
- * Water Inlet: 2" FNPT
- * Filtered Water Outlet: 1/2" press to fit.
- * Air Requirement: none
- * Backwash Cycle Time: 0 , constant flush

Options:

- ozone bubbler for storage tank
 - removes dyes not filtered
 - prevents biological growth